

PRODOTTO	FINITURA	PESO (g/m ²)	ALTEZZA m	LUNG. m	DATI TECNICI	RESISTENZA (N/5 cm)	CODICE	STAMPA
INTERCast FRONTLIT M1	opaco	510	1,12	30	20*20 1000*1000 D	2200/1900	CT-FL510-11L3	E L U
	opaco	510	1,37	30	20*20 1000*1000 D	2200/1900	CT-FL510-13L3	E L U
	opaco	510	1,60	30	20*20 1000*1000 D	2200/1900	CT-FL510-16L3	E L U
	opaco	510	3,20	50	20*20 1000*1000 D	2200/1900	CT-FL510-32L5	E L U
	opaco	510	1,12	30	20*20 1000*1000 D	2200/1900	CT-FL510-11L3-B1	E L U
	opaco	510	1,37	30	20*20 1000*1000 D	2200/1900	CT-FL510-13L3-B1	E L U
	opaco	510	1,60	30	20*20 1000*1000 D	2200/1900	CT-FL510-16L3-B1	E L U
	opaco	510	3,20	50	20*20 1000*1000 D	2200/1900	CT-FL510-32L5-B1	E L U
	opaco	560	1,12	30	28*28 500*500 D	2200/1900	CT-FL560-11L3	E L U
	opaco	560	1,37	30	28*28 500*500 D	2200/1900	CT-FL560-13L3	E L U
INTERCast BLACKBACK	opaco con retro nero	510	1,12	30	20*20 1000*1000 D	2200/1900	CT-FLBB510-11L3	E L U
	opaco con retro nero	510	1,37	30	20*20 1000*1000 D	2200/1900	CT-FLBB510-13L3	E L U
	opaco con retro nero	510	1,60	30	20*20 1000*1000 D	2200/1900	CT-FLBB510-16L3	E L U
	opaco	560	1,12	30	28*28 500*500 D	2200/1900	CT-FL560-11L3	E L U
INTERCast BLOCKOUT	opaco	440	1,12	30	36*36 250*250 D	1800/1030	CT-BK440-11L3	E L U
	opaco	440	1,37	30	36*36 250*250 D	1800/1030	CT-BK440-13L3	E L U
	opaco	440	1,60	30	36*36 250*250 D	1800/1030	CT-BK440-16L3	E L U
	opaco	610	1,12	30	28*28 500*500 D	1850/1350	CT-BK610-11L3	E L U
	opaco	610	1,37	30	28*28 500*500 D	1850/1350	CT-BK610-13L3	E L U
	opaco	610	1,60	30	28*28 500*500 D	1850/1350	CT-BK610-16L3	E L U
INTERCast MESH COATED	opaco con liner	300	1,12	30	12*12 1000*1000 D	1250/1100	CT-MS300-11L3-FR	E L U
	opaco con liner	300	1,37	30	12*12 1000*1000 D	1250/1100	CT-MS300-13L3-FR	E L U
	opaco con liner	300	1,60	30	12*12 1000*1000 D	1250/1100	CT-MS300-16L3-FR	E L U
FUSION FRONTLIT LAMINATO	opaco high smooth	440	1,12	30	18*12 300*500 D	650/590	BL-FLHS440-11L3	E L U
	opaco high smooth	440	1,12	50	18*12 300*500 D	650/590	BL-FLHS440-11L5	E L U
	opaco high smooth	440	1,37	30	18*12 300*500 D	650/590	BL-FLHS440-13L3	E L U
	opaco high smooth	440	1,37	50	18*12 300*500 D	650/590	BL-FLHS440-13L5	E L U
	opaco high smooth	440	1,60	30	18*12 300*500 D	650/590	BL-FLHS440-16L3	E L U
	opaco high smooth	440	1,60	50	18*12 300*500 D	650/590	BL-FLHS440-16L5	E L U

E Eco-solvent L Latex U UV | disponibili su richiesta con certificazione EN 13501-1 | M1 disponibili su richiesta con certificazione M1